

Teleprompters **MASTER SERIES**

The **Master Series** is our range of high bright broadcast monitors, suitable for use in any environment.

Featuring a brightness of 1500 nits and contrast of 1000:1, the monitors are clearly readable in any light. The 4:3 aspect ratio reduces the scanning movement of the reader's eyes to a minimum, while an in-built tally showing camera status and optional numbered tally and clock accessories further improve the talent's experience.

With HD-SDI, composite, and HDMI video inputs, the monitors are compatible with all video scroll engines, and are the perfect partner to the latest Autocue QBox v6.

Using a proven design, with robust and versatile on-camera mounting system options already deployed by hundreds of broadcasters worldwide, the Master Series teleprompters are an ideal fit for users looking to upgrade video prompting workflows.

Key features

- Accepts all standard video inputs
- Easy to read with high brightness and high contrast
- Ideal partner to QBox v6 scroll engine
- Proven, versatile hardware



Optional Accessories

CUE-DIGITALCUE: Master Series Digital Cue Light and Sensor. With selectable camera number and red/green display.

MT-CLOCK/LTCVITC: Digital Clock - LTC and VITC. Mounts to the hood and displays LTC or VITC times in the present's eye-line.

MON-TFM/22/001: 22" HD-SDI talent feedback monitor kit, including mount.



MASTER SERIES 17"



MASTER SERIES 20"



Brightness	1500 nits	1500 nits
Contrast	1000:1	1000:1
Resolution	1280x1024	1280x1024
Dimensions	376 x 316 x 90mm 14.8 x 12.4 x 3.5"	414 x 342 x 90mm 16.3 x 13.5 x 3.5"
Connectivity	HD/SD-SDI, CVBS, HDMI, VGA	HD/SD-SDI, CVBS, HDMI, VGA
Monitor Weight	3.25 kg / 7.2 lb	3.85 kg / 8.5 lbs
Power input	IEC type C14, 100 - 240VAC, 50 - 60 HZ 4-pin XLR, 12VDC ±5%	IEC type C14, 100 - 240VAC, 50 - 60Hz 4-pin XLR, 12VDC ±5%
Power consumption	50W Max	50W Max
Power output	IEC type F, 100 - 240VAC, 50 - 60Hz, 2A Max	IEC type F, 100 - 240VAC, 50 - 60Hz, 2A Max